

OSRAM DULUXSTAR

8W / 11W / 15W / 20W / 23W

Sales Argument

- Lasts up to 8000 Hours, 8 Times the life of an incandescent lamp
- More Compact T3 3U Stick Glass Burner
- Up to 80% Energy Savings compared with similar conventional Incandescent Lamp
- Flicker-free light output
- Environmentally Friendly - Low Mercury Content (<2.5mg) per lamp



Product Details

	DULUXSTAR T3 8W		DULUXSTAR T3 11W		DULUXSTAR T3 15W		DULUXSTAR T3 20W		DULUXSTAR T3 23W	
Voltage (V)	220~240		220~240		220~240		220~240		220~240	
Frequency (Hz)	50/60		50/60		50/60		50-60		50/60	
Wattage (W)	8 (±10%)		11 (±10%)		15 (±10%)		20 (±10%)		23 (±10%)	
Light Color	827	865	827	865	827	865	827	865	827	865
Luminous Flux (lm)	450	430	620	580	900	870	1200	1180	1400	1380
Efficacy (lm/W)	53	50	55	52	60	57	60	57	61	60
Color Rendering	80	80	80	80	80	80	80	80	80	80
Ave.Life Time (hrs)	8000		8000		8000		8000		8000	
Switching Cycles	≥4000		≥4000		≥4000		≥4000		4000	
Lamp Current (mA)	≤80		≤110		≤150		≤ 200		≤230	
Power Factor	0.55		0.55		0.55		0.55		0.55	
Lamp Length E27 (mm)	112 ±3		122 ±3		142 ±2		158 ±3		173 ±3	
Enclosure Diameter(mm)	40 ±1		40 ±1		40 ±2		48 ±1		48 ±1	
Weight (g)	55		55		60		80		85	
Glass Tube	T3 (9mm)		T3 (9mm)		T3 (9mm)		T3 (9mm)		T3 (9mm)	
Number of bulbs	3U		3U		3U		3U		3U	
Instant Start	Yes		Yes		Yes		Yes		Yes	

Additional Information: OSRAM DULUXSTAR Stick complies with:

- IEC 60968 Safety Requirements
- IEC 60969 Performance Requirements
- EN 55015 /61547 RFI & Immunity