



LEDVANCE

LEDVANCE.COM



Inspired by then – perfect today

The Vintage Edition 1906

The design classic for your applications

www.ledvance.com/1906

LEDVANCE
OSRAM



OSRAM
OSRAM





New – for more than 100 years

Since 1906, the OSRAM brand has continuously offered cutting-edge lighting solutions – offered in the best quality and designed to meet users' needs. Inspired by the style used in the year the brand came to life, the Vintage Edition 1906 is now available: Aesthetic lighting solutions with reduced, linear industry design and outfitted with the latest lighting technology. Working in tandem, the lamp and PenduLum Pro, create a valuable luminaire.

A classic – in style, use and price

High-tech products with a retro look have never been so popular! The Vintage Edition 1906 can light all kinds of spaces, like showrooms, hospitality areas and private homes. It is the ideal way to meet today's lifestyle needs and enjoy all sorts of real benefits:






- Four classic lamp forms – Globe, Edison, Oval and Tubular
- Atmospheric discreet light
- With proven halogen or the latest LED technology
- Up to 80 % energy-cost savings produced by LED technology¹
- Flexible light-source positioning thanks to PenduLum Pro design

¹ Compared with standard halogen lamps.



The Vintage Edition 1906



Item name	Product number (EAN)	W ¹		lm ¹	K	R _a	 ²		 [mm]	 d [mm]	t [h] ³
1906ED4W/824FIL	4058075066038	4	E27	380	2400	≥80	NO	300	145	64	15000
1906GL4W/824FIL	4058075066052	4	E27	380	2400	≥80	NO	300	173	125	15000

DIMMABLE

1906ED6.5W/824FIL	4058075066076	6.5	E27	650	2400	≥80	YES	300	145	64	15000
1906GL6.5W/824FIL	4058075066090	6.5	E27	650	2400	≥80	YES	300	173	125	15000

PRODUCT BENEFITS

- Perfect for decorative installations
- Clear lamps with innovative LED "filament" technology
- Lower thermal output (compared with the standard reference product)
- Can be easily fitted instead of ordinary light bulbs
- Instant 100 % light, no warm-up time
- Very low energy consumption
- No UV and near-IR radiation in the light beam

PRODUCT FEATURES

- Dimmable function included with 6.5W
- Super efficient: >100lm/W
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Voltage: 220-240V, Frequency: 50/60Hz
- Instant brightness
- UV and IR radiation free
- Mercury free
- Fit with E27 lamp holders

1. All technical parameters apply to the entire lamp. Because of the complex manufacturing process for light-emitting diodes (LEDs), the specified typical values for LED technical parameters represent only purely statistical variables. They do not necessarily correspond to the actual technical parameters for each individual product which can deviate from the typical value

2. LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

3. The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC62612). The lifetime is estimated at room temperature (25 ° C), free air burning, base up burning position and at rated voltage

The Vintage Edition 1906



Compatibility performance with dimmer ⁶ (connect with up to 4 lamps)

L / Leading edge dimmer		T / trailing edge dimmer		U / Universal Dimmer		
Dimming range < 80%		Dimming range ≥ 80%		Incompatible (flick)		
	Brand	Model	Load Range [W]	Type	Dimming range (%)	Flickering at low dim values
1	LUMEX	LOADSMART LT1D450LS	450W	U	5%-95%	YES
2	Clipsal	32E450UDM	450W	U	15%-95%	NO
3	Clipsal	32ELEDM	400W	LED	5%-95%	NO
4	Schneider-Clipsal	KB31RD400/ FB31RD400	400W	L		YES
5	Shuttle	SDIM-T-LED 500W	500W	T	15%-95%	YES
6	Shuttle	SDIM-T-LED-R 500W	500W	T	15%-95%	YES
7	MK branded	K1541 WHI	75-500W			YES
8	Veto	VT-500	60-500W			YES
9	Siemens	5UH8122-3NC01	25-400W	L	15%-95%	YES
10	Schneider-Clipsal	E8431EPD4	25-350W	L	5%-80%	YES

- All technical parameters apply to the entire lamp. Because of the complex manufacturing process for light-emitting diodes (LEDs), the specified typical values for LED technical parameters represent only purely statistical variables. They do not necessarily correspond to the actual technical parameters for each individual product which can deviate from the typical value
- LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there
- The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC62612). The lifetime is estimated at room temperature (25 ° C), free air burning, base up burning position and at rated voltage

The Vintage Edition 1906



Application Note

- Suitable for indoor application.
- Switch off the light during installation
- For outdoor applications and operation in damp locations special approved fixture are required.
- Input voltage: 220-240V
- Storage temperature & humidity conditions (-20°C up to +80°C, at max. 95% relative humidity)
- Operating temperature & humidity conditions (-20°C up to +40°C, at max. 95% relative humidity)

Lamp conformity

- IEC 62560 Self-ballasted LED-lamps for general lighting services by voltage > 50 V – Safety specifications
- IEC 62778/ GB/T20145 Photo biological safety of lamps
- EN 55015 Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
- EN 61000-3-2 Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
- EN 61000-3-3 Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
- EN 61547 Equipment for general lighting purposes - EMC immunity requirements



Disposal information

- Lamps with WEEE sign can be returned at specific collection points.
- LED lamps have to be disposed as special waste.

