

OSRAM DULUXSTAR HIGH WATTAGE High Output (HO) 28W / 45W / 65W

Sales Argument

- Lasts up to 6000 Hours, 6 Times the life of an incandescent lamp
- More Compact Half Spiral Glass Burner
- Up to 80% Energy Savings compared with similar conventional Incandescent Lamp
- Aim at Professional Market (Wholesales/ Trade/Projects) with High Output (HO) requirement
- Flicker-free light output
- Environmentally Friendly - Low Mercury Content



Product Details

	Duluxstar HW High Output 28W		Duluxstar HW High Output 45W		Duluxstar HW High Output 65W	
Voltage (V)	220~240		220~240		220~240	
Frequency (Hz)	50/60		50/60		50/60	
Wattage (W)	28 (±10%)		45 (±10%)		65 (±10%)	
Light Color (CCT)	827	865	827	865	827	865
Luminous Flux (lm)	1800	1700	2850	2850	4200	4000
Efficacy (lm/W)	64	62	62	62	65	62
Color Rendering (CRI)	80		80		80	
Ave. Life Time (hrs)	6000		6000		6000	
Switching Cycles	≥ 3000		≥ 3000		≥ 3000	
Lamp Current (mA)	≤280		≤450		≤650	
Power Factor	0.5		0.5		0.55	
Length (mm) E27	176 ± 3mm		235 ± 5mm		230 ± 3mm	
Housing Diameter (mm)	58 ± 1		72 ± 2		80 ± 2	
Glass Burner Diameter	58 ± 2		77 ± 3		96 ± 3	
Glass Burner Shape	Half Spiral (12mm)		Half Spiral (14.5mm)		Half Spiral (16mm)	
Mercury(Hg) Content (mg)	≤2.5		≤4.5		≤4.5	
Weight (g) (est.)	150		250		320	
Instant Start	Yes		Yes		Yes	

Additional Information: OSRAM DULUXSTAR HO HS complies with:

- IEC 60968 Safety Requirements
- IEC 60969 Performance Requirements
- IEC 55015 Radio Frequency Interference
- IEC 61547 Immunity