

Established in 1988, LITAFLEX is the pioneer for Corrugated Flexible Conduit in Asia. Through Litaflex's state of art manufacturing facility and quality consistency, Brand 'A2', has positioned itself as a premium and reliable brand in the market.

A2's ingenious design promotes high flexibility and impact strength for protecting and organizing of wire harnesses, harness assemblies, loose cable bundles and other wire installations.

CHARACTERISTICS

- UV Stabilized for Asia's harsh weather conditions
- Eco-friendly: Low Smoke, Zero Halogen and Phosphorus
- High impact and compression strength. Recovers if crushed
- Does not kink
- Temperature resistance: From -40 °C to 140 °C
- Excellent resistance to most acids and chemicals
- Material: Polypropylene (PP)
- Manufactured to IEC 61386-22: 2002
- User-friendly Packaging: Easy drawing of Corrugated Flexible Conduits in a self-contained packaging.



PP CORRUGATED FLEXIBLE CONDUITS

| Product | D | iameter | Standard | Packing |
|---------|-------|---------|----------|---------|
| No. | Outer | Inner | Coil | Export |
| FC 16 | 16mm | 12mm | 50M | 5 |
| FC 20 | 20mm | 16mm | 50M | 5 |
| FC 25 | 25mm | 20mm | 50M | 5 |

Physical Properties of LITAFLEX Conduit Material

| Product | Units | Thermoplastics |
|---------------------|----------|----------------|
| Density | g/cm³ | 0.9 |
| Yield Strength | kg/cm² | 280 |
| Ultimate Strength | kg/cm² | 400 |
| Ultimate Elongation | % | 800 |
| Flexual Modulus | kg/cm² | 12000 |
| Notched (-20°C) | kg-cm/cm | 5 |
| Rockwell Hardness | R scale | 86 |
| HDT (46kgf/cm²) | °C | 112 |
| Shrinkage MD/TD | 1/ 1000 | 15/ 14 |
| Water Absorption | - | negligible |

CORRUGATED CONDUIT FITTINGS

| Corrugated/Plain Connector | | |
|----------------------------|------|---------|
| Product | Size | Packing |
| FCF 20CP | 20mm | 100pc |
| FCF 25CP | 25mm | 100pc |

| Corruga | ited Angle | Adapter |
|----------|------------|---------|
| Product | Size | Packing |
| FCF 20AA | 20mm | 100рс |
| FCF 25AA | 25mm | 100рс |



| 0 | Corrugated Adapter | | |
|----------|--------------------|------|---------|
| | Product | Size | Packing |
| | FCF 20CA | 20mm | 100рс |
| - 1997 - | FCF 25CA | 25mm | 100рс |

| | Corru | gated Conr | ector |
|---|----------|------------|---------|
| U | Product | Size | Packing |
| | FCF 20CC | 20mm | 100рс |
| | FCF 25CC | 25mm | 100рс |

| Corrugated Gland | | |
|------------------|------|---------|
| Product | Size | Packing |
| FCF 16CG | 16mm | 100рс |
| FCF 20CG | 20mm | 100рс |
| FCF 25CG | 25mm | 100рс |

Litaflex Plastics Mfg Pte Ltd

10 Senoko Drive, Singapore 758198 Tel: (65) 6759 1101 Fax: (65) 6759 1121 Email: info@litaflex.com.sg Website: www.litaflex.com.sg